

PRODUCT DATA

WOOD SEALER

DESCRIPTION

Allchem Wood Sealer is a water-based urethane dispersion wood finish that cures to a high gloss, durable and tough finish. Synthetic detergents and emulsifiers have little effect on this product's gloss and durability.

INSTRUCTIONS

Previously Finished Floors: **PREPARATION:**

1. Dust mop floor to remove dust, sand & debris.
2. Clean floor with **Allchem Neutral Cleaner**. A previously sealed floor can be cleaned with an automatic scrubber.
3. Roughen and dull the old finish by using a single disc floor buffer (175 RPM) and a fresh black stripping pad or a 120-grit screen. One screen is required for every 500 sq. Feet (250 sq. ft. per side). Overlap each pass slightly to insure complete even coverage.
4. Mop the floor with **Allchem Neutral Cleaner** then rinse until all dust and residue has been removed. Allow drying completely.

APPLY FINISH:

1. Using a clean synthetic applicator, apply thin, even coats with the grain of the wood. Allow 1-hour dry time between coats. Humid conditions will necessitate longer dry time.
2. It is not always necessary to screen the first coat. If however, the grain has raised or the coat has dried for longer than 4 hours, additional screening may be required. If so, screen the floor with a previously used 120-grit screen or a fresh black stripping pad. Always vacuum and tack thoroughly after screening.

PRODUCT DATA

WOOD SEALER

TIPS TO AVOID A BAD FINISH:

1. Turn air handlers off while applying Allchem Wood Sealer. You want to maintain a wet edge during application. Air movement will adversely affect this edge. Block air movement from under doorways with towels if necessary.
2. After application is complete, wait 10 minutes and turn air handlers on. 10 minutes should be sufficient to allow top to skin over, reducing the possibility of any dust settling on to the film. Air movement will enhance dry time.

FEATURES

Coverage: Up to 1000 sq. ft. per gallon, 1-2 hours recoat time and it cures in 24 hours.

SPECIFICATIONS

Appearance:	Off White Emulsion	pH:	8.9
Odour:	Low		
Specific gravity:	1.03		

PACKAGING: 4 x 1 Gallon, 5 Gallon

ITEM CODE: FLO411

SAFETY

Keep out of reach of children! Product harmful if swallowed. Contact physician immediately. For skin or eye contact, flush area with clear water for 15 minutes. For eye contact, consult physician immediately. Consult Material Safety Data Sheet for further information

PRODUCT DATA

WOOD SEALER

DISCLAIMER

AllChem Limited does not accept responsibility for misuse of this product or injuries/damages that may occur due to failure in adhering to the safety precautions outlined on this document.